

## 

## **Ocular LTE PLUS**



OC20-BC-7.2KW-Plus / OC20-BC-22KW-Plus

Easy configuration to any charging network

OCA & OCPI official member

Live charging feedback

Indoor and Outdoor Rated

Wall or stand mountable

The Ocular LTE The Ocular Home EV Charging Station combines a beautiful, compact charging station with a classleading LCD screen for live charging feedback. Control your home charging station remotely for in-depth insights via an app.

## **Main Features**

**Unique Design** 3.5" LCD display for excellent clarity and LED indicator

**Mobile App Identification** User Authentication via Bluetooth Mobile App

**Smart Grid Savings** Schedule your charging times when rates are lower

Smart Network Connectivity Bluetooth connection

**2 different Models** 1-phase 7kW & 3-Phase 22kW available

## Specification

Model	OC20-BC-7.2KW-Plus / OC20-BC-22KW-Plus
Input Voltage & Current	230V±20%, 32A per phase
Frequency (Hz)	50Hz
Charging Connector	Tethered cable
Power Output	7.2kW (1- Phase)   22kW (3- Phase)
Output Voltage	230V±20% per phase
Output Current	32A MAX per phase
Display	3.5" LCD screen
Electrical Protection	Over current, Short circuit, Over voltage, Under voltage, Ground fault, lightning Surge protection, Over temperature, Earth leakage protection
Operating Temperature	-30°C to +55°C in operation
Storage Temperature	-40°C to +75°C in storage
Working Humidity	95% relative humidity, non-condensing
Internal RCD	Type A + 6mA DC
IP Performance	IP66
Meter	Meter IC
Standby power consumption	<8W
Mounting type	Wall Mountable
Charging Cable Length	6m
Dimension (H x W x D, mm)	295 x 195 x 65mm
Net Weight	7.7kg
Recommended circuit breaker	40A single phase type A RCBO   40A three phase type A RCBO
Recommended cable size (50m run)	10mm2 2C+E   10mm2 4C+E
Certificate	CE, TUV, FCC, CSA, RoHS, RCM
Warranty	2 years
	CHARGE CHARGE POINT INTERFACE

